

What is claimed is:

1. A process for producing a purified aqueous hydrogen peroxide solution comprising contacting an aqueous hydrogen peroxide solution containing metal ion
5 impurities
firstly with a H^+ type cation exchange resin,
secondly with a carbonate ion (CO_3^{2-}) type or
bicarbonate ion (HCO_3^-) type anion exchange resin, and
thirdly with a H^+ type cation exchange resin.
10
2. A process for producing a purified aqueous hydrogen peroxide solution comprising contacting an aqueous hydrogen peroxide solution containing metal ion
impurities
15 firstly with a H^+ type cation exchange resin,
secondly with a fluoride ion (F^-) type anion exchange
resin,
thirdly with a carbonate ion (CO_3^{2-}) type or bicarbonate
ion (HCO_3^-) type anion exchange resin, and
20 fourthly with a H^+ type cation exchange resin.
3. The process for producing a purified aqueous hydrogen peroxide solution as claimed in claim 1 or 2, wherein the aqueous hydrogen peroxide solution is

09540 0544
04450 205560

contacted with an adsorption resin before contacted with the H^+ type cation exchange resin.

4. The process for producing a purified aqueous
5 hydrogen peroxide solution as claimed in any one of
claims 1 to 3, wherein said H^+ type cation exchange
resin is regenerated by repeating a process, 2 or more
times, in which the cation exchange resin is treated
with a downward flowing inorganic acid aqueous solution
10 and then washed with ultra-pure water.

5. The process for producing a purified aqueous
hydrogen peroxide solution as claimed in any one of
claims 1 to 4, wherein the carbonate ion (CO_3^{2-}) type or
15 bicarbonate ion (HCO_3^-) type anion exchange resin is
regenerated by repeating a process, 2 or more times, in
which the anion exchange resin is treated with a sodium
carbonate or sodium bicarbonate aqueous solution and
then washed with ultra-pure water.

20

6. The process for producing a purified aqueous
hydrogen peroxide solution as claimed in any one of
claims 2 to 5, wherein the fluoride ion (F^-) type anion
exchange resin is regenerated by repeating a process, 2

or more times, in which the anion exchange resin is treated with at least one fluorine compound aqueous solution selected from the group consisting of sodium fluoride, potassium fluoride and ammonium fluoride and
5 then washed with ultra-pure water.

7. The process for producing a purified aqueous hydrogen peroxide solution as claimed in any one of claims 3 to 6, wherein the adsorption resin is
10 regenerated by treating with an alcohol aqueous solution as a regenerant and then washing with ultra-pure water.

8. The process for producing a purified aqueous
15 hydrogen peroxide solution as claimed in any one of claims 1 to 7, wherein the hydrogen peroxide concentration in the aqueous hydrogen peroxide solution is 40 to 70 % by weight.

20 9. The process for producing a purified aqueous hydrogen peroxide solution as claimed in any one of claims 1 to 8, wherein said purified aqueous hydrogen peroxide solution is obtained by filtrating a solid impurities contained in the aqueous hydrogen peroxide

09855107 051407

solution to which a flocculating agent has been preliminary added, by a fine filter.

10. The process for producing a purified aqueous
5 hydrogen peroxide solution as claimed in claim 9,
wherein said flocculating agent is at least one
phosphorus based compound selected from the group
consisting of phosphoric acid, polyphosphoric acid,
acidic sodium pyrophosphate,
10 aminotri(methylenephosphoric acid) and salt thereof,
and ethylenediaminetetra(methylenephosphoric acid) and
salt thereof.
11. The process for producing a purified aqueous
15 hydrogen peroxide solution as claimed in claim 10,
wherein said phosphorus based compound is added in an
amount that the atomic ratio (Al/P) of the Al ion
impurity contained in the aqueous hydrogen peroxide
solution in terms of a metal atom Al to the phosphorus
20 based compound in terms of a phosphorus atom is 0.045
or less.
12. The process for producing a purified aqueous
hydrogen peroxide solution as claimed in any one of

claims 9 to 11, wherein the fine filter has an average pore size of 0.2 μm or less.

09540 0440
0450 0550